

[Order Now](#)[SDK](#)[Product Folder](#)[Support](#)

BOLT-2020MRS

20MP NIR Monochrome MIPI Camera based on Onsemi Hyperlux™ LP AR2020 Sensor

Vadzo Bolt-2020MRS is a 20MP MIPI Camera based on Onsemi Hyperlux™ LP AR2020 Imaging Sensor. The camera comes with inherent capabilities such as enhanced dynamic range (eDR), excellent Low-Light and NIR Sensitivity. The camera delivers max resolution of 20MP and Video streaming of 4K, 1080p and 720p. The camera comes with a M12/S-Mount lens holder that supports a 74DFOV lens by default. The camera supports image capture and video streaming in Y8 format, and store in BMP format. Bolt-2020MRS can be integrated with solutions based on platforms such as Raspberry Pi, Nvidia Nano, Nvidia XavierNX, etc.

Key Features

- Sensor Model: AR2020 Onsemi Hyperlux™ LP
- Max Resolution: 20MP
- Pixel Size: 1.4 µm x 1.4 µm
- Shutter: Rolling Shutter
- Lens FOV: 74 DFOV
- Compliance: RoHS 3, REACH



Applications

- **Machine Vision Cameras:** Quality Inspection, Assembly Line Monitoring, Object Recognition and Classification, Surface Inspection, High-Speed Imaging.
- **Smart Surveillance Camera:** Iris Recognition, Day/Night Video Recording, Smart Parking.
- **Medical Devices:** Digital Pathology, Digital Microscopes, Ophthalmic Devices, Fluorescence Imaging.

INDEX

1. Introduction	3
2. Camera Specifications	3
3. Supported Resolutions	4
4. Supported Camera Functions	5
5. MIPI Interface	5
6. Status LED	5
7. Temperature and Humidity Specifications	5
8. Dimensions	6
Base Board Top Side – 2D	6
ATR Board: 4-Lane Bottom Side – 2D	6

1. Introduction

Bolt-2020MRS is a NIR Fixed-Focus Monochrome camera based on Onsemi AR2020 sensor. The camera incorporates the Onsemi Hyperlux™ LP AR2020 low-noise CMOS sensor that supports key features like enhanced HDR, Excellent NIR Response @850n and 900nm, Wake on Motion, and so on. In addition to this, the ISP also supports Auto functions such as Auto-Exposure. The camera supports 4-lane MIPI CSI-2 Interface and has been tested with platforms such as Raspberry PI, Nvidia Nano, and Nvidia XavierNX.

2. Camera Specifications

General Information	
Product Family	Bolt Series
Camera Model	Vadzo Bolt-2020MRS
Sensor	
Sensor	AR2020 CMOS sensor from Onsemi
Sensor Format	1/1.8"
Pixel Size	1.4µm x 1.4µm
Max Resolution	20MP - 5120(H) x 3840(V)
Shutter	Rolling Shutter
Chroma	Mono
Camera Data	
Interface	4 Lane MIPI CSI-2
Pixel Depth	8bit / 10bit
Output Format	Y8 and Y12
Exposure Control	Manual Control via software & Auto-Exposure
GPIO	2x NC
Camera Hardware	
Lens	S Mount (M12 Standard)
MIPI connector	XF3M(1)-1515-1B (2 Lane) & 54548-2271 (4 Lane)

Power Requirement	Max: 1.45 W at 3.3VDC Min: 0.80 W at 3.3VDC
Operating Temperature	-30°C to 70°C
Dimension	38mm (L) x 38mm (B) convertible to 32mm (L) x 32mm (B)
Weight	18 Grams (Without Lens)
Camera Software	
Video Resolutions	VGA, 720p, 1080p, 4K, 5K and 20MP (5120x3840).
Video formats	Y8
Image Capture formats	BMP and Y8
Image Capture Modes	Software trigger
OS Supported	Windows, Linux.
Conformity	
Conformity	RoHS 3 and REACH

3. Supported Resolutions

Resolution	4-Lane MIPI CSI-2 Frame Rates (FPS)
	Y8
640 x 480 (VGA)	240
1280 x 720 (HD)	120
1920 x 1080 (FHD)	120
3840 x 2160 (4K)	30
5120x2880 (5K)	20
5120 x 3840 (20MP)	10

4. Supported Camera Functions

The List of functions supported by the Bolt-2020MRS camera are:

- Resolution Control
- Image Format Setting
- Video Format Setting – Y8 and Y12
- Image Capture Software Trigger
- Gain – Auto & Manual
- Exposure – Auto & Manual
- Anti Flicker – 50Hz/60Hz

5. MIPI Interface

The camera module supports both 4-Lane MIPI CSI 2 as well as 2-Lane MIPI CSI 2 interface. Vadzo has designed the camera hardware such that it can be directly integrated with Raspberry PI as well Nvidia Jetson development kit via the 2-Lane MIPI CSI 2 interface. Vadzo has used the XF3M (1)-1515-1B from Omron for this interface.

Vadzo has integrated the capability of functioning in the 4-Lane MIPI CSI 2 bandwidth as well to ensure that you can achieve faster frame rates.

6. Status LED

Status LEDs indicate the below:


- Red Mono indicates Device is powered ON with no Streaming.
- Yellow Mono indicates: Camera is currently Streaming.

7. Temperature and Humidity Specifications


Description	Specification
Operating Temperature	-30 ⁰ C to 70 ⁰ C
Storage Temperature	-30 ⁰ C to 70 ⁰ C
Humidity	20% to 80%, Relative, non-condensing.

8. Dimensions

Base Board Top Side – 2D



ATR Board: 4-Lane Bottom Side – 2D



IMPORTANT NOTICE AND DISCLAIMER

Vadzo Imaging products are sold by description only. Vadzo Imaging reserves the right to change the information in this document, including URL references and/or specifications is subject to change without notice. Customers should obtain the latest relevant information and data sheets before placing orders and should verify that such information is current and complete.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

THIS DOCUMENT IS PROVIDED AS IS WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY WARRANTY OTHERWISE ARISING OUT OF ANY PROPOSAL, SPECIFICATION, OR SAMPLE.

All liability, including liability for infringement of any proprietary rights, relating to the use of information in this document is disclaimed. No licenses express or implied, by estoppel or otherwise, to any intellectual property rights are granted herein.

All trade names, trademarks, and registered trademarks mentioned in this document are the property of their respective owners and are hereby acknowledged.



Copyright © 2017–2026 Vadzo Imaging. All Rights Reserved.