

[Order Now](#)[SDK](#)[Product](#)[Support](#)

FALCON-234CGA

2MP Color Autofocus USB 3.0 UVC Camera based on Onsemi AR0234 Sensor

Vadzo Falcon-234CGA is a 1080p global shutter Autofocus USB 3.0 Camera based on Onsemi AR0234 Sensor coupled with a high-performance ISP. The camera delivers a max resolution of 2MP and Video streaming of 1080p@60fps, 720p@60fps, and VGA@90fps. The camera comes with an S Mount Lens with VCM-Based Autofocus Capability that supports 32DFOV lens. You can stream video in YUV422 and MJPEG format and capture images in BMP and JPEG format.

Key Features

- Sensor Model: AR0234 Onsemi Sensor
- Max Resolution: 2MP
- Pixel: 3.0 μ m x 3.0 μ m
- Shutter: Global Shutter
- Lens FOV: 32DFOV
- Compliance: UVC, RoHS 3, REACH



Applications

- **Robotics Camera:** Object Scanning, Document Scanning, OCR, Obstacle Detection.
- **Smart Surveillance Camera:** Facial Recognition, Day/Night Video Recording, Smart Parking, Pedestrian Safety.
- **Kiosk Camera:** Document Scanning, OCR, Barcode Reading, Facial Recognition, Demography Analysis.
- **Digital Signage Camera:** Document Scanning, OCR, Barcode Reading, Facial Recognition, Demography Analysis.

INDEX

1. Introduction	3
2. Camera Specifications	3
3. Supported Resolutions	5
4. Supported Camera Functions	5
5. USB 3.0 Interface	5
6. Status LED	6
7. General-Purpose I/O Lines	6
8. Temperature and Humidity Specifications	6
9. Dimensions	7
Board Top Side – 2D.....	7
Board Bottom Side - 2D	7
USB Board Top Side – 2D	8
USB Board Bottom Side – 2D	8

1. Introduction

Falcon-234CGA is a UVC-compliant USB 3.0 Fixed-Focus Global Shutter color camera based on the Onsemi AR0234 sensor. The camera is designed to be backward compatible with USB 2.0 as well.

The camera incorporates the AR0234 Bayer sensor from Onsemi integrated with an on-board Image Signal Processor (ISP) to perform functions such as Auto functions such as Auto-Focus, Auto-Exposure, and Auto-White Balance, debayering, demosaicing, color correction, contrast correction, gamma correction, denoising, lens corrections, and so on. The camera works in USB 3.0 Super Speed mode and USB 2.0 High Speed mode.

The Image Signal Processor is integrated with the USB 3.0 controller to provide a UVC-compliant USB 3.0 camera. The USB controller is also programmed to support the HID Pipeline which shall support UVC extension functions that are not supported in the standard UVC drivers.

2. Camera Specifications

General Information	
Product Family	Falcon series
Camera Model	Vadzo Falcon-234CGA
Sensor	
Sensor	AR0234 sensor from Onsemi
Sensor Format	1/2.6"
Pixel Size	3.0 µm x 3.0 µm
Max Resolution	2MP – 1920(H) x 1200(V)
Shutter	Global Shutter
Chroma	Color
Camera Data	
Interface	USB 3.2 Gen1 is Backward compatible with USB 2.0
Pixel Depth	8bit / 10bit
Output Format	YUV422 and MJPEG

Exposure Control	Manual Control via software & Auto-Exposure
GPIO	6 pins. NC.
Camera Hardware	
Lens	S Mount Lens with VCM-Based Autofocus Capability
USB connector	Type C
GPIO connector	Present
Power Supply	USB powered
Power Requirement	Max: 1.75 W at 5VDC Min: 1.05 W at 5VDC
Operating Temperature	-40 ⁰ C to 85 ⁰ C
Dimension	38mm (L) x 38mm (B) convertible to 32mm (L) x 32mm (B)
Weight	13 Grams
Camera Software	
Video Resolutions	VGA, HD, and FHD
Video formats	YUV422 and MJPEG
Still Image Resolutions	VGA, HD, and FHD
Image Capture formats	BMP and JPEG
Image Capture Modes	Software Trigger
UVC Camera Controls	Brightness, Exposure, Contrast, Sharpness, Saturation, Gamma, Gain, White Balance
Additional Controls	ROI-based Auto-Exposure, JPEG Compression Control, Denoising, Flip
OS Supported	Windows, Linux, Android (need additional SDK)
Conformity	
Conformity	UVC Compliant, RoHS 3, REACH

3. Supported Resolutions

Resolution	Frame Rates (FPS) in USB 3.0 Mode
	YUV
640 x 480 (VGA)	90
1280 x 720 (HD)	60
1920 x 1080 (FHD)	60

4. Supported Camera Functions

The List of functions supported by the Falcon-234CGA camera are:

- Resolution Control
- Image Format Setting
- Video Format Setting – YUV422 & MJPEG
- Image Capture Software Trigger
- Gain – Auto & Manual
- Exposure – Auto & Manual
- White Balance – Auto & Manual
- Anti Flicker – 50Hz/60Hz
- Contrast Control
- Gamma Control
- Hue & Saturation Control
- Sharpness Control

5. USB 3.0 Interface

The camera module's USB 3.0 connector is a standard USB Type C connector. It provides a nominal 5 Gbit/s SuperSpeed data transfer connection to supply power to the device and to transmit video data and control signals. The power supply must comply with the Universal Serial Bus 3.0 Specification. The nominal operating voltage is 5 VDC, effective on the camera module's connector.

Connection assignments and numbering adhere to the Universal Serial Bus 3.0 standard. USB Certified 3.0 Gen 1 or higher cables to be used. Vadzo does not recommend non-certified USB cables.

6. Status LED

Status LEDs indicate the below:

- Red color indicates the Device is powered ON with no Streaming.
- The yellow color indicates the camera is currently Streaming.

7. General-Purpose I/O Lines

GPIO lines are terminated through Six (6) pin socket connectors from Würth Elektronik part number 665306124022. Refer to the below table for GPIO Connector Pin Numbering and Assignments.

Pin	Line	Function
1	Power	Do not use.
2	-	Do not use*
3	-	Do not use*
4	Input1	General Purpose I/O (GPIO) line with 1.8V tolerant directly connected to MCU Preset: Input Line
5	Output1	General Purpose I/O (GPIO) line with 1.8V tolerant directly connected to MCU Preset: Output Line
6	GND	Ground

**The Vadzo engineering team shall be able to enable the IOs on the firmware level as per the end user technical requirements under the purview of the Vadzo Imaging customisation program.*


Recommended mating connector from Würth Elektronik part number 665006113322.

8. Temperature and Humidity Specifications


Description	Specification
Operating Temperature	-40 ⁰ C to 85 ⁰ C
Storage Temperature	-40 ⁰ C to 85 ⁰ C
Humidity	20% to 80%, Relative, non-condensing.

9. Dimensions


Board Top Side – 2D




Board Bottom Side - 2D



USB Board Top Side – 2D



USB Board Bottom Side – 2D



IMPORTANT NOTICE AND DISCLAIMER

Vadzo Imaging products are sold by description only. Vadzo Imaging reserves the right to change the information in this document, including URL references and/or specifications is subject to change without notice. Customers should obtain the latest relevant information and data sheets before placing orders and should verify that such information is current and complete.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

THIS DOCUMENT IS PROVIDED AS IS WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY WARRANTY OTHERWISE ARISING OUT OF ANY PROPOSAL, SPECIFICATION, OR SAMPLE.

All liability, including liability for infringement of any proprietary rights, relating to the use of information in this document is disclaimed. No licenses express or implied, by estoppel or otherwise, to any intellectual property rights are granted herein.

All trade names, trademarks, and registered trademarks mentioned in this document are the property of their respective owners and are hereby acknowledged.



Copyright © 2017–2026 Vadzo Imaging. All Rights Reserved.